版本号	更改位置	更改内容	更改人	更改日期	审核

70g双胶纸; 展开尺寸462*240mm; 成型尺寸66*120mm; 双面印刷; 风琴折再对折

折线

英语

66

120

USER MANUAL


GS VISION

UWELL CALIBURN G5 VISION

©2026 By SHENZHEN UWELL TECHNOLOGY CO., LTD.
All Rights Reserved.

ENGLISH

1. Product Introduction



1. Mouthpiece
2. Cartridge
3. Fill Plug
4. Device
5. Airflow Control
6. Display Screen
7. Button
8. USB Type-C Port


2. Product Specification

Materials	304 SS、ABS+ABS	E-liquid Capacity	5.5 mL /3.0 mL
Dimensions	19.24 × 29.3 × 19.84 mm (.76) (.04)	Maximum Output Power	30W
	18.89 × 28.3 × 18.64 mm (.74)	Battery Capacity	1600 mAh
Cartridge Resistance	0.4Ω (1.1-1.5W)/ 0.6Ω (1.1-1.2W)	Net weight	50.1g

3. Quick Start Guide

1. Remove the mouthpiece or open the fill plug. Fill the cartridge with e-liquid through the fill port. Reinstall the mouthpiece or close the fill plug. Let it sit for 10 minutes before vaping.
2. Remove the cartridge and peel off the insulating film from the bottom.
3. Reinstall the cartridge and device.
4. Press the button 5 times within 2 seconds to turn on the device. Inhale through the mouthpiece to vape.

4. Filling the Cartridge



ITALIAN

GERMAN

FRENCH

PORTUGUESE

русский

POLISH

SPANISH

Precautions:
a. Insert the e-liquid bottle nozzle fully into the fill port before filling.
b. Close the fill plug or mouthpiece immediately after filling to help prevent leakage.
c. Do not vape if the cartridge is empty to avoid damaging the coil.
d. When using a new cartridge for the first time, allow it to sit for 10 minutes after filling so the coil can fully absorb the e-liquid. This helps prevent dry hits and damage to the coil.

5. Vaping
Inhale through the mouthpiece to vape.

6. Button Settings

6.1 Screen Wake-Up
When the device is powered on, press the button once to wake the screen. The screen stays on for 10 seconds.

6.2 Mode Switching
Press the button three times quickly to switch between STORM and NIGHT modes.

6.3 Power Adjustment
Press the button three times quickly to enter power adjustment mode. Then press the button to adjust the output power.
STORM mode: (10-30 W), (10-25 W), (10-20 W), and (10-15 W).
NIGHT mode: (10-15 W), (10-12.5 W), (10-11 W), and (10-9 W).

6.4 Power On/Off
Press the button five times quickly to turn the device on or off.

7. Low-Battery Protection
When the battery level reaches 0 while vaping, "00" flashes 3 times, and the device will stop firing.

8. Timeout Protection
If a draw lasts longer than 8 seconds, the power display area flashes 3 times, and the device will stop firing.

9. Short-Circuit Protection
If a short circuit is detected, the entire screen flashes 3 times, and the device will not fire.

10. Open-Circuit Protection
If an open circuit is detected, the corresponding icon flashes 3 times, and the device will not fire.

11. Cartridge Connection Indicator
When the cartridge is removed or inserted, the screen displays the corresponding removal or insertion animation, then returns to the main screen.

12. Charging
When the device is connected to a power adapter, the charging icon flashes and the current battery level is displayed. Once charging is complete, the battery level stays solid.

Important Information:
1. Use only a high-quality, safety-certified power adapter (5V/2A) and a compatible USB Type-C cable for charging.
2. When traveling by air, remove the cartridge from the device and pack it separately. Changes in cabin pressure may cause e-liquid leakage.
3. Avoid using or storing the device in extreme heat, direct sunlight, corrosive materials, water, humidity, and extreme cold. Do not carry the device with metal objects, as this may cause a short circuit. To help extend the service life of the device, charge it at least once a month.
4. Do not use the device in environments with strong static electricity.

DUTCH

DANISH

العربية

正面

背面

技术要求及规格：

- 材　　质: 70g双胶纸
- 表面处理: /
- 要　　求:双面印刷,风琴折再对折
- 印刷颜色: K
- 完成后外尺寸: 66*120mm
- 未标注尺寸公差: ±0.5mm
- 注意事项: 无少印,错印,颜色正确,字迹清晰;
  不能有色差,啤穿底纸,溢胶,套色不准等现象;
  需要符合RoHS要求。

优维尔	KPN049套装说明书(英语)				
	日期	/	表面处理	/	
	名称	说明书	零件编号	/	
	材质	/	物料编码	/	
视角:	单位: MM	比例: 1:1	共1页 第1页	版本	A/0
设计:	审核:		批准:		